

HF | HIDROFORCE

semichemical fluting type high performance

CEPI code: 61

Characteristics:

- 100% recycled fluting with very high performance.
- The most rigid paper in the Saica paper range.
- Alternative to semi-chemical papers.
- Excellent machinability and bonding.

Applications:

- Uses with large resistance requirements in humid environments.
- Sustainable packaging.
- Export and overseas fruit and vegetable market.
- Climatic chambers, frozen goods.



100% recycled
and recyclable
papers

HF | HIDROFORCE

semichemical fluting type high performance



* For contact conditions and/or special instructions, see our Declaration of Conformity.

target characteristics

TEST	STANDARD	UNIT	HIDROFORCE		
Nominal basis weight	ISO 536	g/m ²	145	160	170
Nominal moisture index	On-line	%	9	9	9
SCT, CD	ISO 9895	kN/m	4,1	4,5	4,7
		kN.m/kg	28	28	27,5
CMT 30/50, MD*	EN ISO 7263	N	363	400	425
		N.m ² /g	2,5	2,5	2,5
CCT 30/50, CD	ISO 16945	N	3,2	3,5	3,7
		N.m ² /g	22	22	22

guaranteed characteristics

TEST	STANDARD	UNIT	HIDROFORCE		
Nominal basis weight	ISO 536	g/m ²	145	160	170
Mean basis weight			nominal ± 3%		
Nominal moisture index	On-line	%	9	9	9
Mean moisture index			nominal -1+0,5		
SCT, CD	ISO 9895	kN/m	3,8	4,2	4,4
		kN.m/kg	26,5	26,5	26
CMT 30/50, MD*	EN ISO 7263	N	319	352	374
		N.m ² /g	2,2	2,2	2,2
CCT 30/50, CD	ISO 16945	kN/m	2,9	3,2	3,4
		kN.m/kg	20	20	20
Production centre			SP	SP	SP

The index guaranteed values refer to the nominal basis weight.



Access the complete and always updated file.

Valid from October 2025.