

# ONDULIGHT

## recycled fluting

CEPI code: 60



The mechanical performance of this 100% recycled paper allows its utilisation to optimise not only board grades but also pack design, for a complete packaging solution cost optimisation.



100% Recycled and responsibly manufactured paper

## target characteristics

TEST	STANDARD	UNIT	ONDULIGHT		
Nominal basis weight	ISO 536	g/m <sup>2</sup>	<b>85</b>	<b>90</b>	<b>100</b>
Nominal moisture index	ISO 287	%	8	8	8
SCT, CD	ISO 9895	kN/m	1,57	1,70	1,80
		kN.m/kg	18	18	18
CMT 30/50, MD	EN ISO 7263	N	130	150	170
		N.m <sup>2</sup> /g	1,5	1,6	1,7

## guaranteed characteristics

TEST	STANDARD	UNIT	ONDULIGHT		
Nominal basis weight	ISO 536	g/m <sup>2</sup>	<b>85</b>	<b>90</b>	<b>100</b>
Variation			nominal ± 3%		
Nominal moisture index	ISO 287	%	8	8	8
Variation			nominal + 1% -1,5%		
SCT, CD	ISO 9895	kN/m	1,40	1,50	1,62
		kN.m/kg	16	16	16
CMT 30/50, MD	EN ISO 7263	N	115	130	150
		N.m <sup>2</sup> /g	1,3	1,4	1,5

The index guaranteed values refer to the nominal basis weight.